



JJ GLOBAL PRODUCTS CATALOG

#3401



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	2520mmx940mmx1135mm
Meters	Electronic instrument with dashboard
Controller	48V 12MOS
Rear Axle	Split rear axle
Front brake	31 shock absorption / front brake 110
Rear brake	130 drum brake
Gradeability	15°
Headlight	Ordinary large bulb
Ground clearance	130mm
Curb weight	140KG
Loading capacity	160KG
other option	Including: high mounted brake lamp and independent hand brake.
Rim	Iron wheel
E-Motor	48V500W
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 Km/h
Tires(F/R)	300-12/300-12
Mileage per Charge	60
Battery	A Lead-acid batteries
Color	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Certification	CCC
Charging time	8-10h
Loading in 40HQ	110 sets/40HQ CKD

#3402



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	2630mm*980mm*1305mm
Meters	Electronic instrument with dashboard
Controller	48V 12MOS
Rear Axle	Split rear axle
Front brake	31 shock absorption / front brake 110
Rear brake	130 drum brake
Gradeability	15°
Headlight	Ordinary large bulb
Ground clearance	130mm
Curb weight	170KG
Loading capacity	200KG
other option	Including: high mounted brake lamp and independent hand brake.
Rim	Iron wheel
E-Motor	48V500W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 Km/h
Tires(F/R)	3.00-12/3.00-12
Mileage per Charge	60
Battery	A Lead-acid batteries
Color	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Certification	CCC
Charging time	8-10h
Loading in 40HQ	72 sets/40HQ CKD

#3403



#3403

promotion version



ITEM	SPECIFICATIONS
Overall Size	2740mm*1030mm*1240mm
Meters	Electronic instrument with dashboard
Controller	48V 15MOS
Rear Axle	Split rear axle
Front brake	31 shock absorption / front brake 110
Rear brake	130 drum brake
Gradeability	15°
Headlight	Ordinary large bulb
Ground clearance	135mm
Curb weight	185KG
Loading capacity	300KG
other option	Including: high mounted brake lamp and independent hand brake.
Rim	Iron wheel
E-Motor	48V650W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 Km/h
Tires(F/R)	3.00-12/3.00-12
Mileage per Charge	60
Battery	48V52A Lead-acid batteries
Color	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Certification	CCC
Charging time	8-10h
Loading in 40HQ	72 sets/40HQ CKD

#3404



#3404

promotion version



#3404

37 external spring shock absorber/ front brake 110



ITEM	SPECIFICATIONS
Overall Size	2945mm*1050mm*1365mm
Meters	Electronic instrument with dashboard
Controller	48V 18MOS
Rear Axle	Integrated rear axle
Front brake	37 shock absorption / front brake 110
Rear brake	160 drum brake
Gradeability	15°
Headlight	Ordinary large bulb
Ground clearance	140mm
Curb weight	200KG
Loading capacity	500KG
other option	Including: high mounted brake lamp and independent hand brake.
Rim	Iron wheel
E-Motor	48V800W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 Km/h
Tires(F/R)	3.75-12/3.75-12
Mileage per Charge	65/75
Battery	60V52A Lead-acid batteries
Color	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Certification	CCC
Charging time	8-10h
Loading in 40HQ	60 sets/40HQ CKD

#3405



#3405

promotion version
(37 Shock absorption/front
brake 110)



#3405

high railing version



#3405

plus version
(3140mm*1170mm*1360mm)



ITEM

SPECIFICATIONS

Overall Size	3060mm*1200mm*1350mm
Meters	Electronic instrument with dashboard
Controller	48V 18MOS
Rear Axle	Integrated rear axle
Front brake	37 external spring damping / front brake 110
Rear brake	160 drum brake
Gradeability	15°
Headlight	Ordinary large bulb
Ground clearance	160mm
Curb weight	218KG
Loading capacity	600KG
other option	include : the light of Hight-Location Brake , Individual handbrake
Rim	Iron wheel
E-Motor	48V800W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 km/h
Tires(F/R)	3.75-12/3.75-12
Mileage per Charge	65/75
Battery	60v52A Lead-acid batteries
Color	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Certification	CCC
Charging time	8-10h
Loading in 40HQ	54 sets/40HQ CKD

#3406



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	3125mm*1175mm*1790mm
Meters	Electronic instrument with dashboard
Controller	48V 18MOS
Rear Axle	Integrated rear axle
Front brake	37 external spring damping / front brake 110
Rear brake	160 drum brake
Gradeability	15°
Headlight	Ordinary large bulb
Ground clearance	160mm
Curb weight	236KG
Loading capacity	600KG
other option	include : the light of Hight-Location Brake 、 Individual handbrake
Rim	Iron wheel
E-Motor	48V800W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 km/h
Tires(F/R)	3.75-12/3.75-12
Mileage per Charge	65/75
Battery	60v52A Lead-acid batteries
Color	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Certification	CCC
Charging time	8-10h
Loading in 40HQ	54 sets/40HQ CKD

#3407



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	3330mm*1298mm*1440mm
Meters	Electronic instrument with dashboard
Controller	24MOS
Rear Axle	Integrated rear axle
Front brake	43 shock absorption / front brake 130
Rear brake	180 drum brake
Gradeability	15°
Headlight	Ordinary large bulb
Ground clearance	170mm
Curb weight	280KG
Loading capacity	1500KG
other option	Including: high mounted brake lamp and independent hand brake.
Rim	Iron wheel
E-Motor	60V1200W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 Km/h
Tires(F/R)	4.00-12/4.50-12
Mileage per Charge	60
Battery	60V120A Water battery
Color	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Certification	CCC
Charging time	8-10h
Loading in 40HQ	40 sets/40HQ CKD

#3408



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	3495mm*1298mm*1450mm
Meters	Electronic instrument with dashboard
Controller	30MOS
Rear Axle	Full floating rear axle
Front brake	43 shock absorption / front brake 130
Rear brake	220 drum brake
Gradeability	15°
Headlight	Ordinary large bulb
Ground clearance	180mm
Curb weight	287KG
Loading capacity	1500KG
other option	Including: high mounted brake lamp and independent hand brake.
Rim	Iron wheel
E-Motor	60V1500W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 Km/h
Tires(F/R)	4.00-12/4.50-12
Mileage per Charge	60
Battery	60V120A Water battery
Color	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Certification	CCC
Charging time	8-10h
Loading in 40HQ	36 sets/40HQ CKD

#3409



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	3700mm*1400mm*1480mm
Meters	Electronic instrument with dashboard
Controller	DATAI 30 tubes
Rear Axle	Integrated full floating rear axle
Front brake	50 shock absorption / front brake 130
Rear brake	220 drum brake
Gradeability	15°
Headlight	Ordinary large bulb
Ground clearance	200mm
Curb weight	330kg
Loading capacity	1800KG
other option	Including: high mounted brake lamp and independent hand brake.
Rim	Iron wheel
E-Motor	60V 2000W
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 Km/h
Tires(F/R)	500-12/500-12
Mileage per Charge	60
Battery	60V120A Water battery
Color	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Certification	CCC
Charging time	8-10h
Loading in 40HQ	36 sets/40HQ CKD

#3410



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	2960mm*1105mm*1680mm
Meters	Electronic instrument with dashboard
Controller	48V 18MOS
Rear Axle	Integrated rear axle
Front brake	130
Rear brake	160 drum brake
Gradeability	15°
Headlight	LED
Ground clearance	160mm
Curb weight	284KG
Loading capacity	600KG
other option	include : the light of Hight-Location Brake , Individual handbrake
Rim	Iron wheel
E-Motor	48V800W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 km/h
Tires(F/R)	3.75-12/3.75-12
Mileage per Charge	65/75
Battery	60v52A Lead-acid batteries
Color	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Certification	CCC
Charging time	8-10h
Loading in 40HQ	10-12 sets/40HQ CBU, 24 sets/40HQ CKD(Detachable cab)

#3411



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	3060mm*1160mm*1680mm
Meters	Electronic instrument with dashboard
Controller	48V 18MOS
Rear Axle	Integrated rear axle
Front brake	130
Rear brake	160 drum brake
Gradeability	15°
Headlight	LED
Ground clearance	160mm
Curb weight	288KG
Loading capacity	700KG
other option	include : the light of Hight-Location Brake , Individual handbrake
Rim	Iron wheel
E-Motor	48V800W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 km/h
Tires(F/R)	3.75-12/3.75-12
Mileage per Charge	65/75
Battery	60V52A Lead-acid batteries
Color	8-10h
Certification	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Charging time	CCC
Loading in 40HQ	10-12 sets/40HQ CBU, 24 sets/40HQ CKD(Detachable cab)

#3412



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	3160mm*1160mm*1660mm
Meters	Electronic instrument with dashboard
Controller	24MOS
Rear Axle	Integrated rear axle
Front brake	37 external spring shock absorber
Rear brake	160 drum brake
Gradeability	15°
Headlight	LED
Ground clearance	1000KG
Curb weight	160mm
Loading capacity	300KG
other option	Including: high mounted brake lamp and independent hand brake.
Rim	Iron wheel
E-Motor	60V1200W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 Km/h
Tires(F/R)	3.75-12/4.00-12
Mileage per Charge	60
Battery	60v52A Lead-acid batteries
Color	8-10h
Certification	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Charging time	CCC
Loading in 40HQ	5-6 sets/40HQ CBU, 20 sets/40HQ CKD(Detachable cab)

#3413



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	3260mm*1500mm*1660mm
Meters	Electronic instrument with dashboard
Controller	24MOS
Rear Axle	Integrated rear axle
Front brake	37 external spring shock absorber
Rear brake	180 drum brake
Gradeability	15°
Headlight	LED
Ground clearance	1000KG
Curb weight	170mm
Loading capacity	340KG
other option	Including: high mounted brake lamp and independent hand brake.
Rim	Iron wheel
E-Motor	60V1200W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 Km/h
Tires(F/R)	4.00-12/4.50-12
Mileage per Charge	60
Battery	60V120A Water battery
Color	8-10h
Certification	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Charging time	CCC
Loading in 40HQ	5-6 sets/40HQ CBU, 20 sets/40HQ CKD(Detachable cab)

#3414



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	3495mm*1360mm*1700mm
Meters	Electronic instrument with dashboard
Controller	30MOS
Rear Axle	Integrated full floating rear axle
Front brake	43 external spring shock absorber
Rear brake	220 drum brake
Gradeability	15°
Headlight	LED
Ground clearance	1500KG
Curb weight	180mm
Loading capacity	370KG
other option	Including: high mounted brake lamp and independent hand brake
Rim	Iron wheel
E-Motor	60V1500W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 Km/h
Tires(F/R)	400-12/450-12
Mileage per Charge	60
Battery	60V120A Water battery
Color	8-10h
Certification	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Charging time	CCC
Loading in 40HQ	5-6 sets/40HQ CBU, 20 sets/40HQ CKD(Detachable cab)

#3415



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	3650mm*1450mm*1900mm
Meters	Electronic instrument with dashboard
Controller	DATAI controller
Rear Axle	Integrated full floating rear axle
Front brake	50 external spring shock absorption
Rear brake	220 drum brake
Gradeability	15°
Headlight	LED
Ground clearance	1800KG
Curb weight	180mm
Loading capacity	500KG
other option	Including: high mounted brake lamp and independent hand brake
Rim	Iron wheel
E-Motor	60V2000W/2200W Shift motor DATAI system
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 Km/h
Tires(F/R)	500-12/500-12
Mileage per Charge	60
Battery	60V120A Water battery
Color	8-10h
Certification	LIGHT BLUE, GREEN, SILVER, RED, TEAL, BLUE
Charging time	CCC
Loading in 40HQ	5-6 sets/40HQ CBU, 20 sets/40HQ CKD(Detachable cab)

#3416



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	2930mm*1060mm*1695mm
Meters	Electronic instrument with dashboard
Controller	48V 18MOS
Rear Axle	Integrated rear axle
Front brake	130
Rear brake	160 drum brake
Gradeability	15°
Headlight	LED
Ground clearance	600KG
Curb weight	160mm
Loading capacity	320KG
other option	include : the light of Hight-Location Brake , Individual handbrake
Rim	Iron wheel
E-Motor	48V800W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 km/h
Tires(F/R)	3.75-12/3.75-12
Mileage per Charge	65/75
Battery	60v52A Lead-acid batteries
Color	8-10h
Certification	LIGHT BLUE, GREEN, RED, WHITE
Charging time	CCC
Loading in 40HQ	8 sets/40HQ CBU, 20 sets/40HQ CKD(Detachable cab)

#3417



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	3240mm*1200mm*1700mm
Meters	Electronic instrument with dashboard
Controller	24MOS
Rear Axle	Integrated rear axle
Front brake	37 external spring shock absorption
Rear brake	160 drum brake
Gradeability	15°
Headlight	LED
Ground clearance	1000KG
Curb weight	180mm
Loading capacity	360KG
other option	Including: high mounted brake lamp and independent hand brake.
Rim	Iron wheel
E-Motor	60V1200W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 Km/h
Tires(F/R)	3.75-12/4.00-12
Mileage per Charge	60
Battery	60V120A Water battery
Color	8-10h
Certification	LIGHT BLUE, GREEN, RED, WHITE
Charging time	CCC
Loading in 40HQ	4 sets/40HQ CBU, 16 sets/40HQ CKD(Detachable cab)

#3418



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	3050mm*1160mm*1750mm
Meters	Electronic instrument with dashboard
Controller	48V 18MOS
Rear Axle	Integrated rear axle
Front brake	130
Rear brake	160 drum brake
Gradeability	15°
Headlight	Ordinary large bulb
Ground clearance	600KG
Curb weight	160mm
Loading capacity	265KG
other option	include : the light of Hight-Location Brake , Individual handbrake
Rim	Iron wheel
E-Motor	48V800W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 km/h
Tires(F/R)	3.75-12/3.75-12
Mileage per Charge	65/75
Battery	60V52A Lead-acid batteries
Color	8-10h
Certification	LIGHT BLUE, GREEN, RED, WHITE
Charging time	CCC
Loading in 40HQ	48 sets/40HQ CKD

#3419



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	3240mm*1200mm*1770mm
Meters	Electronic instrument with dashboard
Controller	Large 18 tubes
Rear Axle	Integrated rear axle
Front brake	130
Rear brake	160 drum brake
Gradeability	15°
Headlight	Ordinary large bulb
Ground clearance	800KG
Curb weight	180mm
Loading capacity	300KG
other option	include : the light of Hight-Location Brake , Individual handbrake
Rim	Iron wheel
E-Motor	60V1000W Shift motor
Front Suspension	Shock absorber with hydraulic
Rear Suspension	Rear shock absorption of reinforced steel plate spring
Max speed	45 km/h
Tires(F/R)	3.75-12/3.75-12
Mileage per Charge	65/75
Battery	60V120A Water battery
Color	8-10h
Certification	LIGHT BLUE, GREEN, RED, WHITE
Charging time	CCC
Loading in 40HQ	30 sets/40HQ CKD

#3420



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	2920mm*1200mm*1820mm
Instrument	Electronic instrument with dashboard
Controller	60V 30MOS
Rear Axle	Integrated rear axle
Front brake	//
Rear brake	180 drum brake
Gradeability	15°
Headlight	LED
Loading Capacity	D+2+3 persons
other option	with Fan, Radio, Endoscope, High brake light, Independent handbrake.
Rim	Iron wheel
E-Motor	60V1500W
Shock absorber in front	Aluminum cylinder hydraulic shock absorber
Rear Suspension	Increase leaf spring shock absorption
Max speed	35 km/h
Tires(F/R)	4.00-12/4.00-12
Mileage per Charge	65/75
Battery	60V52A Lead-acid batteries
Charging time	8-10h
Color	RED
Certification	CCC
Loading in 40HQ	4 sets/40HQ CBU

#3421



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	2190mm*1140mm*1620mm
Instrument	Electronic instrument with dashboard
Controller	48V15MOS
Rear Axle	Integrated rear axle
Front brake	110
Rear brake	160 drum brake
Angle of Gradeability	15°
Headlight	LED
Loading Capacity	D+2 persons
other option	with Fan, Radio,Endoscope, High brake light,Independent handbrake.
Rim	Iron wheel
E-Motor	48V650W
Shock absorber in front	Aluminum cylinder hydraulic shock absorber
Rear Suspension	Increase leaf spring shock absorption
Max speed	35 km/h
Tires(F/R)	350-10
Mileage per Charge	65/75
Battery	60v52A Lead-acid batteries
Charging time	8-10h
Loading in 40HQ	10 sets/40HQ CBU

#3422



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	2520mm*1210mm*1650mm
Instrument	Electronic instrument with dashboard
Controller	48V 18MOS
Rear Axle	Integrated rear axle
Front brake	110
Rear brake	160 drum brake
Angle of Gradeability	15°
Headlight	LED
Loading Capacity	D+2 persons
other option	with Fan, Seat belt, Radio, Endoscope, High brake light, Independent handbrake
Rim	Aluminum
E-Motor	48V800W
Shock absorber in front	Aluminum cylinder hydraulic shock absorber
Rear Suspension	Increase leaf spring shock absorption
Max speed	35 km/h
Tires(F/R)	4.00-10/4.00-10
Mileage per Charge	65/75
Battery	60v52A Lead-acid batteries
Charging time	8-10h
Loading in 40HQ	5 sets/40HQ CBU

#3423



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	2800*670*1180mm
Meters	Electrical with Dashboard
Controller	72V 24MOS
Rear Axle	Integrated rear axle 160
Front brake	13 hydraulic shock absorption
Rear brake	220mm diameter hydraulic drum brake
Angle of Gradeability	15°
Headlight	Ordinary large bulb
Loading Capacity	D+3 persons
other option	with Fan,Seat belt, Radio,Endoscope, High brake light,Independent handbrake.
Rim	Aluminum
E-Motor	60V1000W brushless DC motor
Shock absorber in front	Aluminum cylinder hydraulic shock absorber
Rear Suspension	Increase leaf spring shock absorption
Max speed	35 Km/h
Tires(F/R)	375-12/375-12
Mileage per Charge	80km
Battery	60V80ah Lead-acid
Charging time	8-10h
Loading in 40HQ	25sets/40HQ CKD

#3424



Reference Pictures

ITEM	SPECIFICATIONS
Overall Size	2930*116*178mm
Meters	Electrical with Dashboard
Controller	72V 30MOS
Rear Axle	Integrated rear axle
Front brake	180mm diameter disc brake
Rear brake	220mm diameter hydraulic drum brake
Angle of Gradeability	15°
Headlight	Ordinary large bulb
Loading Capacity	D+3 persons
other option	with Fan,Seat belt, Radio,Endoscope, High brake light,Independent handbrake.
Rim	Aluminum
E-Motor	60V1500W brushless DC motor
Shock absorber in front	Aluminum cylinder hydraulic shock absorber
Rear Suspension	Increase leaf spring shock absorption
Max speed	35 Km/h
Tires(F/R)	4.00-12/4.00-12
Mileage per Charge	80km
Battery	60V80ah Lead-acid
Charging time	8-10h
Loading in 40HQ	25sets/40HQ CKD

#3425

Refrigerator Cargo Tricycle



ITEM	SPECIFICATIONS
Overall Size	1150*3100*1830mm
Meters	Electronic LCD instrument
Controller	Large 18 tube controller
Rear Axle	Integrated rear axle
Front brake	130 drum brake
Rear brake	160 drum brake
Angle of Gradeability	15°
Headlight	LED
Loading Capacity	250KG
Rim	Iron wheel
E-Motor	60V1000W
Shock absorber in front	37 tubes hydraulic
Rear Suspension	65mm
Max speed	35km/h
Tires(F/R)	375-12/375-12
Mileage per Charge	60
Battery	60v65ah(driving motor), 48v45ah(freezing system)
Charging time	10-12h
Loading in 40HQ	\



THANKS

✉ inquiry@jinjian-global.com

🌐 <https://www.jj-ev.com/>

📍 Apt.514, 12th Building, Guo Bincheng, Jin Shan Road, Yu Bei District, Chongqing City, China